

Applicant: Rata Ilkka  
PCT App. No.: PCT/FI2004/050006

### Remarks

Claims 12–32 remain pending in the application.

¶ [0028] has been amended to add the following:

A portion of a front part of the blade holder forming the blade clamp 33 defines the gap 32 for receiving the blade 16. The front part defines at least one fastening point for the backing blade 18, the fastening point forming a longitudinally extending groove which has a larger portion for receiving the form-locking detent 34 and a first smaller portion extending in a direction overlying the gap 32.


This disclosure is based on ¶ [0027], ¶ [0029] and FIG. 2a.

¶ [0030] has been amended to note that “Preferably there are remarkably fewer reinforced fibers extending in the cross-machine direction than extending in the ~~longitudinal~~ lateral direction of the machine.” This paragraph has also been amended to note that “the major part of reinforced fibers is found extending in the lateral ~~longitudinal~~ direction of the machine, in which case the treatment equipment can be loaded against the surface.” These corrections to ¶ [0030] are supported by the disclosures of ¶ ¶ [0030] and [0031] and do not introduce new matter.

Applicant: Rata Ilkka  
PCT App. No.: PCT/FI2004/050006

Applicant believes that no new matter has been added by these amendments and that the application, as amended, is ready for examination. Favorable action thereon is respectfully solicited.

Respectfully submitted,



---

Patrick J. G. Stiennon, Reg. No. 34934  
Attorney for Applicant  
P.O. Box 1667  
Madison, Wisconsin 53701-1667  
(608) 250-4870  
Amdt1.app

10/542074

JC20 Rec'd PCT/PTO 13 JUL 2005

In The United States Patent And Trademark Office

Applicant: Rata Ilkka

Date: July 13, 2005

Date Filed: Simultaneously herewith

Docket No.: METSO-43

PCT App. No.: PCT/FI2004/050006

For: Composite-Construction Treatment Equipment


**Certificate of Express Mailing**

I hereby certify that this document is being deposited with  
the United States Postal Service "Express Mail Post Office to  
Addressee" service under 35 C.F.R. §1.10

on 7/13/05

with Mailing Label No. EV 728 025 681 US

and is addressed to the Commissioner for Patents, P.O. Box  
1450, Alexandria, VA 22313-1450



Signature

Patrick J. G. Stiennon, Reg. No. 33934

Name of applicant, assignee or Registered Representative

Marked Up Copy of Substitute Specification under 37 C.F.R. 1.125(b)(2)

~~COMPOSITE-CONSTRUCTION TREATMENT EQUIPMENT~~

†

**TITLE OF THE INVENTION**

**Composite-Construction Treatment Equipment**

**CROSS REFERENCES TO RELATED APPLICATIONS**

**[0001] This application is a U.S. national stage application of international app. No. PCT/FI2004/050006, filed Jan. 27, 2004, the disclosure of which is incorporated by reference herein, and claims priority on Finnish Application No. 20035010, filed Jan. 30, 2003.**

5

**STATEMENT AS TO RIGHTS TO INVENTIONS MADE UNDER  
FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT**

**[0002] Not applicable.**

## **BACKGROUND OF THE INVENTION**

**[0003]** This invention relates to composite-construction treatment equipment, which is designed to be set in connection with a moving surface and which equipment includes

- 5       - a frame arranged in the vicinity of the said surface,
- a blade holder formed of a composite material as an essentially integral component and connected to the frame,
- a blade adapted to the blade holder, including an edge arranged to be set in contact with the moving surface by moving the blade holder, and
- 10       - a separate backing blade adapted to the blade holder, set to the blade holder by one end while the other end extends closer to the said edge than the blade holder.

**[0004]** In the present treatment equipment blade holders manufactured entirely of a composite material have been in use only for a short period of time. One known  
15 blade holder located in a paper machine has an arm section by which the blade holder is attached to a frame formed by a beam. The arm section is extended with a clamp section, which is fitted with a gap for the blade. A composite-construction blade holder is light in weight and durable compared to conventional metal blade holders. The blade holder can also be made more adaptable to the surface for  
20 example by orientating the reinforced fibers. In spite of this, the blade holder is rigid in the blade loading direction, i.e. in the machine direction. In addition, the composite-construction returns to the original shape even after major deformations.

**[0005]** Conventionally the blade holder is attached to the frame using screws. This requires removing the screws during the installation and change of the blade holder,  
25 which takes time and requires working inside the paper machine. In some cases even the whole treatment equipment needs to be removed from the paper machine for installing the blade holder. In addition, the holes required by the screws in the arm section create discontinuity points in the blade holder construction reducing thus its durability.

t  
t

## SUMMARY OF THE INVENTION



5 [0006] The object of this invention is to provide novel composite-construction treatment equipment, which is easier to use and service, yet more versatile than heretofore. The features characterizing this invention become evident from the appended claims. In the treatment equipment according to the invention, due to the novel design, the whole blade holder can be changed in a simple manner. This makes the installation and change of the blade holder quick and easy. Irrespective of the unexpected construction, the blade holder can additionally be provided with loading elements, for example. The blade holder can also be easily retrofitted in  
10 existing treatment equipment without major modifications. On the other hand, the design of new treatment equipment can be made simpler than before. In addition, with suitable dimensioning and design the components of the treatment equipment can be changed independent of each other, which allows to precisely adjust the treatment equipment characteristics as desired.



15 [0007] The invention is described below in detail by making reference to the enclosed drawings, which illustrate some of the embodiments of the invention, ~~in which~~.







## **BRIEF DESCRIPTION OF THE DRAWINGS**



[0008] †

**Figure** **FIG. 1**  is a side view of the treatment equipment according to the invention arranged in connection with a moving surface.



5      [0009] **Figure** **FIG. 2a**  is an enlarged view of the blade holder illustrated in **Figure** **FIG. 1** .


[0010] **Figure** **FIG. 2b**  is a cross-sectional view of a modification of the blade holder shown in **Figure** **FIG. 2a** without a blade.

10      [0011] **Figures 3a-3d**  **FIGS. 3a, 3b, 3c, and 3d** illustrate various applications of the blade holder according to the invention.

[0012] **Figure** **FIG. 4a**  is a cross-sectional view of the blade holder according to the invention equipped with loading elements.

15      [0013] **Figure** **FIG. 4b**  shows the blade holder of **Figure** **FIG. 4a** only.

[0014] **Figure** **FIG. 5a**  shows another application of the treatment equipment according to the invention.

-  
20      [0015] **Figure** **FIG. 5b**  shows another application of the blade holder equipped with loading elements.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0016] †

~~Figure~~ **FIG. 1** shows the treatment equipment according to the invention adapted in connection with a moving surface 10. Here the moving surface 10 is a paper machine roll 11, of which only a part is shown. Generally the purpose of the treatment equipment is to treat a moving surface. In the doctoring example, the purpose of doctoring is to remove impurities from the surface or, for example, the web itself in some paper machine positions. In paper and board machines and in other forming machines, moving surfaces also comprise the surfaces of various cylinders and fabrics. The treatment equipment is used for example for web coating, in which a coating paste is applied to the surface of a moving web. This is illustrated in ~~Figure~~ **FIG. 5a**. Furthermore, the treatment equipment comprises a frame 12, arranged in the vicinity of the surface 10 to be treated. In ~~Figure~~ **FIG. 1** the frame 12 is a beam 13, which is supported by a shaft 14 in a way that allows pivoting in relation to the paper machine construction. In practice, the beam is locked in the correct position using turnbuckle screws, for example (not shown). On the other hand, the beam can be pivoted towards the surface by means of loading elements for improving the doctoring result.

**[0017]** The treatment equipment also includes a blade holder 15, which is made of a composite material to form an essentially integral component. The advantages of this type of blade holder are described below in greater detail. The blade holder 15 is correspondingly attached to the frame 12 (~~Figure~~ **FIG. 1**). The actual treatment is provided by the blade 16 adapted to the blade holder **15**, the dimensioning and material of which can vary between different applications. In the proposed applications both the doctor blade and the coating blade are described. The blade 16 includes a doctoring edge 17, **shown in FIG. 2A**, which is arranged in contact with the moving surface 10 by moving the blade holder 15. In this way the moving surface is provided with a treatment. ~~Figure~~ **FIG. 1** shows a so-called rigid blade holder 15, in which the movement of the blade holder 15 is created by pivoting the beam 13. The proposed blade holders 15 also comprise a separate backing blade 18,

which is set in the blade holder 15 by one end.

**[0018]** Correspondingly, the other end of the backing blade 18 extends closer to the said edge 17 than the blade holder 15 thus supporting the blade 16. The operation of the backing blade is also described below in greater detail. The blades 16 shown in the figures are new. In a worn blade the edge is to the other direction. On the other hand, a bevel corresponding to a worn blade can in practice be pre-ground to the blade. In ~~f~~**FIGS.** 1 and 5a the movement direction of the surface 10 is indicated by the arrow.

f

†

**[0019]** According to the invention, the blade holder 15 is unexpectedly removably adapted to the frame 12 using a pair of form-locking counter clamps 19. The form-lock between the counter clamps 20 and 21 is additionally arranged tight in the lateral direction of the blade 16 and essentially free in the longitudinal direction of the blade 16. This allows moving the blade holder 15 in the longitudinal direction of the blade, i.e. in the cross direction of the machine. In practice, for example in a paper machine, the blade holder can be installed simply by pushing from the side and correspondingly, it can be removed by pulling it out. In spite of this quick clamping the form-lock is tight in the lateral direction of the blade. This ensures that the blade holder is reliably kept in place in the machine direction. For additional security during the operation, the cross-machine directional mobility can be prevented using a locking pin, for example. On the other hand, this cross-directional mobility can be utilized for oscillation with appropriate material selections. That is, the blade can be moved in relation to the surface by moving the blade holder only. All parts are preferably made of a composite material. Consequently, the scratching effect of metal rivets, for example, can be avoided.

**[0020]** In the proposed treatment equipment the first counter clamp 20 forming the pair of counter clamps 19 is a profiled shoulder. Correspondingly, the second counter clamp 21 is adapted to cover the first counter clamp 20 essentially on the opposite sides. In this way the said second counter clamp 21 forms a groove against

the first shoulder-like counter clamp 20. In principle the location of the counter clamps can vary. However, in the blade holder 15 the counter clamp is preferably arranged in the rear part parallel to the blade holder. In this case the blade is attached to the front part of the blade holder 15. Here the front part refers to the blade holder part, which is nearest to the surface to be doctored. With the proposed construction of the counter clamps, the blade holders can be freely positioned, and the blade holder can be designed optimally as regards loading and blade attachment. At the same time, disadvantageous projections, which would gather impurities and be sensitive to damage, are avoided.

[0021] Existing frames are usually provided with threaded holes for attaching the blade holder. In this case the attachment of the blade holder 15 is easy using an adapter component 22 according to the invention. Generally one of the counter clamps forming the pair of counter clamps is thus arranged in a separate adapter component, which is to be attached to the frame. The fastening screws are illustrated with broken lines in the figures. The first embodiment of the adapter component 22 is illustrated in ~~{Figures}~~FIGS. 1, 2a and 2b. Here the adapter component 22, together with the frame 12, forms the counter clamp 21 for the shoulder-like counter clamp 20 formed in the blade holder 15. The proposed construction is extremely compact, and the adapter component 22 is easy to attach to the frame 12. In addition, the arm sections of even the known composite-construction blade holders can be modified into shoulder-like counter clamps using suitable machining methods. In practice, however, it is more preferable to bring the blade holder to the final state in connection with the manufacture, thus maintaining an integral blade holder construction. The same reference numbers are used for functionally similar parts.

[0022] The following embodiments of the adapter component 22 are shown in ~~{Figures}~~FIGS. 3a and 3b. Here one of the counter clamps 20 or 21 is completely formed in the adapter component 22. In this way the adapter component 22 can be permanently attached to the frame 12. In ~~{Figure}~~FIG. 3a the adapter component 22 is provided with a shoulder-like counter clamp 20 while the groove-like counter

clamp 21 is located in the blade holder 15. This ensures that the form-lock is well protected from impurities. In addition, the blade holder 15 can be designed advantageously as regards the manufacture. In the treatment equipment shown in ~~{Figure}~~FIG. 3a the adapter component 22 ~~has~~ also has a curve 23 for compensating the change of the blade~~{15}~~ position with respect to a conventional blade holder. Due to the adapter component 22 the blade 16 extends closer to the surface 10, in which case the blade angle  $\alpha$  of the blade 16 relative to the surface most often changes. According to ~~{Figure}~~FIG. 1, as the length of the blade holder 15 increases, the blade angle  $\alpha$  decreases, which usually has a negative effect on the doctoring result. This problem can be avoided by moving the blade holder in the vertical direction, or it can be at least avoided by adjusting the beam and its position. If required, the adapter component provided with a curve can be installed in the frame also the other way round. The straightness and shape of the curve can also vary between different applications.

**[0023]** For example, when manufacturing new treatment equipment according to the invention, the adapter component can be excluded. This is possible by arranging one of the counter clamps 20 or 21 forming the pair of counter clamps 19 in the frame 12. This is shown in the embodiments of ~~{Figures}~~FIGS. 3c and 3d. In particular the blade holder 15 shown in ~~{Figure}~~FIG. 3d can be made extremely short, which allows its positioning in confined positions.

**[0024]** Today also adjustable blade holders are used, in which the frame keeps its place as the blade holder turns. In addition to the above-described rigid blade holders, the blade holder according to the invention can also be arranged adjustabl~~ely~~ly. Generally the counter clamps forming the pair of counter clamps are arranged as a mutually functional articulation. In this case it is possible to change the angle between the counter clamps while keeping the locking in the blade's lateral direction unchanged. The embodiment of an adjustable, or rather of a loadable blade holder 15 is shown in ~~{Figure}~~FIG. 4a. The principle of this blade holder 15 is corresponding with that of the blade holder 15 shown in ~~{Figure}~~FIG. 3a, except



that the counter clamp 21 of the blade holder 15 is made more spacious. This ensures that the form-lock is maintained while the movement is still possible. For defining the movement, there are loading elements 24 between the counter clamp 20 and the blade holder 15. In the embodiment shown in ~~{Figure}~~FIG. 4a the loading elements  
5 24 are placed between the adapter component 22 and the blade holder 15.

[0025] The positioning of the loading elements may be difficult due to a confined construction. The lack of space can be avoided by arranging at least one provision in either or both of the counter clamps for the loading elements. In ~~{Figure}~~FIG. 4a the blade holder 15 has such provisions on both sides of the adapter component 22. The  
10 upper provision has a loading hose 26, known as such, and the lower provision has a spring component 27. ~~{Figure}~~FIG. 4b illustrates both the upper provision 25 and the lower provision 25' in more detail. The treatment equipment in question is so adapted that the spring component 27 tends to turn the blade 16 upwards. Correspondingly, the blade 16 can be loaded against the surface by adjusting the  
15 pressure in the loading hose 26. The movement of the blade holder 15 is indicated by the arrow in ~~{Figure}~~FIG. 4a, which shows a solution that is particularly advantageous for new treatment equipment according to the invention. In this case only one loading hose is needed for using the blade holder. For the existing treatment equipment including two loading hoses, a blade holder can be selected, in  
20 which there are provisions for two loading hoses (not shown).

~~{Figure}~~[0026] FIG. 5b shows another embodiment of the loadable blade holder. Here, too, the blade holder 15 movement is provided by means of the loading hose 26. Correspondingly, the returning force is produced by another loading hose 26' or a spring component 27. Here the adapter component 22 extends to both sides of the  
25 frame 12. The fastening is secured with screws.

[0027] The design of the blade holder according to the invention allows using different blades. ~~{Figure}~~FIG. 3a illustrates a thick plastic blade and ~~{Figures}~~FIGS. 3b[-]3d show thin metal or composite material blades. Due to the

blade holder design, thin blades can be fastened using several different methods. In  
[Figure]FIG. 3c a conventional rivet 28 is used, whereas in [Figure]FIG. 3b a  
composite blade has been attached using a special adapter 29. In a similar composite  
blade shown in [Figure]FIG. 3d there is an extension 30 in the rear part that is  
5 larger and different in shape, in which case a separate adapter is not necessary. For  
the blade 16 the blade holder also has a gap 32, defined, besides the backing blade  
18, by the clamp 33.

[0028] In the treatment equipment, the function of the backing blade, too, is  
essential. According to the invention the backing blade 18 is similar to the blade 16.  
10 In addition, the end of the [Figure]backing blade 18, which is to be adapted to the blade  
holder 15, has a form-lockable detent 34 for fastening the backing blade 18  
removably to the blade holder 15. In this way the backing blade, like the blade  
holder, has a quick clamping system, allowing its replacement. Furthermore, in  
selecting and manufacturing the backing blade, it is possible to utilize the know-how  
15 and production methods related to the blades, which simplifies the manufacture of  
the treatment equipment and reduces costs. [Figure]

**Figure]A portion of a front part of the blade holder forming the blade clamp 33  
defines the gap 32 for receiving the blade 16. The front part defines at least one  
fastening point for the backing blade 18, the fastening point forming a  
20 longitudinally extending groove which has a larger portion for receiving the  
form-locking detent 34 and a first smaller portion extending in a direction  
overlying the gap 32.**

[0029] FIG. 2b shows an application related to the backing blade 18. Here the  
blade holder 15 has two fastening points 31 for the detent 34 for adjusting the  
25 position of the backing blade 18 in the lateral direction of the blade 16. That is, the  
blade holder 15 has two alternative fastening points 31 for connecting the backing  
blade 18. In this case it is possible, for example, to use backing blades of two  
different dimensional classes in the blade holder. Secondly, the groove formed by  
the fastening point 31 can be used for example for supplying a lubricant to the blade

and further to the surface to be treated. Also, it is possible to adapt a pipe, for example, in the groove for the lubricant preventing thus application of pressure to the blade holder. In addition, the pipe can be easily sealed and the lubricant dosing is accurate.

5     **[0030]** In total, the manufacture of treatment equipment according to the invention is less complicated than heretofore. Preferably all parts are manufactured using the pultrusion method. This ensures that the components are ready for use without major machining operations. In addition, when using the pultrusion method, reinforced fibers can be set in the component in a specified manner. Preferably there are  
10     remarkably fewer reinforced fibers extending in the cross-machine direction than extending in the ~~longitudinal~~ lateral direction of the machine. In this way the blade, backing blade, blade holder and even the adapter component, if any, adapt to the shapes of the surface to be doctored. That is, the entire treatment equipment is controllably flexible in the cross direction of the machine. This eliminates vibration  
15     problems of the treatment equipment and uneven blade wear, among other things. In addition, the known micro-screws designed for profile control are unnecessary. Instead, the major part of reinforced fibers is found extending in the ~~longitudinal~~ lateral direction of the machine, in which case the treatment equipment can be loaded against the surface. That is, the components are rigid for  
20     transferring the force.

**[0031]** The above-described construction also enables a quick adjustment of the treatment equipment. Various types of blade holders can be attached to the frame and similarly, various types of blades and backing blades can be quickly replaced in the blade holders. In this way it is possible to obtain a suitable combination for each  
25     situation by changing the components. Due to the removable backing blade, the blade holder can additionally be entirely cleaned. This is easy also on the outside of the machine, as the whole blade holder can be simply removed from the machine.

**[0032]** Composite-construction treatment equipment is advantageous as regards



the operation as well. Firstly, for example the tested blade holders weigh only 3 kg/m, in which case bending due to their own weight is nonexistent. In addition, the blade holder can be installed in the treatment equipment manually without cranes or other supports. Furthermore, the composite-construction endures well sudden impacts and returns to the original shape in spite of even major deformations. On the other hand, when damaging, the composite-construction breaks totally at once, functioning thus as a special safety fuse. In case of damage to the blade holder, it can be quickly replaced with a new one without a lengthy unoperative state of the treatment equipment. Damaging also saves other constructions of the treatment equipment. The operation of the treatment equipment can also be easily monitored by installing diaphragm sensors, for example, between the blade and the backing blade for determining the loading pressure profile.

[0033] The treatment equipment according to the invention is simple to manufacture, yet versatile to use. In addition, installing the treatment equipment and changing its components is quick, which reduces production breaks. In particular, the blade holder is light in weight, and therefore its storing and especially handling is easy. Also, in using the blade holder, less force is required than before. Another significant aspect is also the possibility of combining various components into a combination appropriate for each situation. Consequently, the desired doctoring result is obtained in each position, also when the geometry of the position changes, for example, when changing in a certain position a roll, whose diameter differs from that of the previously used roll. In addition, the treatment equipment can be reset during a grade change shutdown even when changing the production parameters, which is impossible in the known treatment equipment.

††

ABSTRACT {

~~OF THE INVENTION RELATES TO~~ HE DISCLOSURE

5 A composite-construction treatment equipment ~~{comprising}~~has a frame (12)  
~~{and}~~with a connected blade holder (15)~~{connected thereto and}~~ made of a  
composite material. ~~{In addition, t}~~The blade holder (15) ~~{is provided with}~~has a  
blade (16) and a separate backing blade (18). The blade holder (15) is removably  
adapted to the frame (12) using a pair of form-locking counter clamps (19). The  
form-lock is arranged tight in the lateral direction of the blade (16) and essentially  
free in the axial direction of the blade (16).